

# MP15

## Vibratory Plates



**WACKER  
NEUSON**  
*all it takes!*



### **This plate proves that performance is valuable**

These Wacker Neuson vibratory plates offers functionality and performance at a real value price. The compact design allows for compaction of mixed soils in the narrowest of spaces even in extremely narrow trenches. The guide handle with vibration damping means longer working hours and less fatigue for the operator.

- Proven design and technology from the world's leading brand Wacker Neuson, tough ductile iron baseplate is extremely durable even under extreme conditions and provides long service life
- Cyclonic 3 stage air-filtration system, Low hand-arm-vibrations
- Ergonomically designed lifting handles make loading and unloading from transport vehicles easier for the operator
- A rugged water tank comes as standard, and leads to higher operator comfort and improved productivity during any asphalt works.
- A rugged water tank comes as standard, and leads to higher operator comfort and improved productivity during any asphalt works, optional wheel kit for easy transportation

## MP15 Technical specifications

### Operating data

Operating weight (without water/fuel)	83 kg
Centrifugal force	15 kN
Base plate size (w × l)	500 × 588 mm
Advance travel max. (depending on soil)	20 m/min
Surface capacity max. (depending on soil)	600 m <sup>2</sup> /h

### Engine / Motor

Engine / Motor type	Air-cooled, single cylinder, 4-cycle gasoline engine
Engine / Motor manufacturer	Loncin-G210F
Displacement	212 cm <sup>3</sup>
Engine performance (max.)	4.4 kW
at rpm	3,600 rpm
Fuel consumption	1 l/h
Tank capacity (water)	8.3 l
Tank capacity (fuel)	3.6 l

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.  
Copyright © 2019 Wacker Neuson SE.